



Customer Service: [1-888-GO-BETCO](tel:1-888-GO-BETCO)
Equipment Tech Support [1-877-856-5954](tel:1-877-856-5954)
8AM - 5:30PM EST, Monday - Friday

Unlock™ Floor Stripper



No-Rinse floor stripper

This high power, high speed floor stripper was developed to penetrate and remove multiple coats of burnished floor finish with a minimum of labor. This fast acting labor saving product requires little, if any scrubbing and greatly reduces the time it takes to strip a floor. This powerful professional stripper requires no neutralizing or flood rinsing after use. This product is suitable for use on most surfaces.

Features

Powerful formula cuts through layers of old finish in minutes
Pleasant to Use: Low to no odor released.
Saves Energy: Works with cold water.
Low Foaming

Available In

4 - 1 Gal. Bottles Item #88804-00

5 Gal Bag in Box Item #888B5-00

Directions for Use

Recommended for removing multiple coats of water-based acrylic floor finishes from all types of resilient tile and hard surfaces. Not recommended on linoleum or sheet vinyl floors. Pre-test in a small area; color bleeding or discoloration may occur on linoleum, rubber tile, or asphalt tile. Sweep or dust mop floor to remove any large debris.

For light to medium stripping, dilute 10 oz. /gal. (1:12).

For heavy stripping, dilute 25 oz. /gal. (1:5) with cool water.

Apply solution liberally to floor surface. Allow 3 - 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low speed rotary machine, automatic scrubber or stripping machine. Pick up solution with a wet vacuum, automatic scrubber or mop and bucket and thoroughly rinse the floor. Allow floor to dry completely before applying finish or sealer. No flood rinsing is necessary if surface appears free of dust and residue.

Tech Specs

Color	Colorless
Flash Point	n/a
Fragrance	None
Freeze/thaw stability	n/a
pH	13.0 - 14.0
Residue on evaporation	None
Specific gravity	1.029
Coverage	400 sq. ft./ gallon
Warranty	2 years