

Formula: Wite-Out® Correction Pen

MSDS/T203175

Page: 1 of 3

April 1, 1999

MATERIAL SAFETY DATA SHEET

Manufacturer

Wite-Out Products, Inc.
145 Southchase Blvd.
Fountain Inn, SC 29644

MSDS Preparer:

SGS U.S. Testing Company, Inc.*
Fairfield, NJ 07004
Tel: (973) 575-5252

*Specific Technical information
provided by manufacturer

Date: April 1, 1999

Supersedes: September 29, 1997

Page 1 of 3

Emergency Telephone No.
800-424-9300 (CHEMTREC)

Information Telephone No.
(203) 783-2103

I. PRODUCT INFORMATION

Identity : Wite-Out® Correction Pen
Synonyms: Wite-Out® Correction Roller, WP-1
Chemical Name : Not Available (N/A)
Chemical Family : N/A
CAS Registry Number : N/A
DOT Shipping Name : Consumer Commodity (As packaged for retail sale)
DOT Hazard Class : ORM-D (As packaged for retail sale)

II. HAZARDOUS INGREDIENTS

<u>Component(s)</u>	<u>%</u>	<u>OSHA PEL</u>	<u>Hazard Information</u>	
			<u>ACGIH TLV</u>	<u>OTHER S</u>
Petroleum Naphtha (CAS #64742-48-9)	40-50	400 ppm	400 ppm	

III. PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point, °F : 204-237 (estimated)
Vapor Pressure (mm Hg) : N/A
Solubility in Water : N/A
Appearance and Odor : Free flowing liquid with petroleum solvent odor
Specific Gravity, (H₂O = 1) : 1.25 (estimated)
Evaporation Rate (Butyl Acetate = 1) : N/A
pH : N/A

IV. FIRE AND EXPLOSION HAZARD DATA

Flammable Liquid : Can release vapors that form flammable mixture at or above flash point.
Flash Point (Method Used) : 22-26°F (Seta Flash Closed Cup)
Flammability Limits in Air, LEL : 1.7
UEL : 12.3
Extinguishing Media for Fires : CO₂, Foam, Dry Chemical

IV. FIRE AND EXPLOSION HAZARD DATA (CONT.)

Special Fire Fighting Procedures : Flammable liquid. Wear self-contained breathing apparatus.
Unusual Fire and Explosion Hazards : Toxic combustion gas may be formed as decomposition products.

V. REACTIVITY DATA

Stability : ☐ Unstable ☒ Stable
Conditions to Avoid : Heat source, sparks or flame.
Materials to Avoid : Strong oxidizing or reducing agents.
Hazardous Decomposition Products : Toxic fumes or gases.
Hazardous Polymerization Products : ☐ May Occur ☒ May Not Occur

VI. HEALTH HAZARD DATA

<u>Carcinogen or Potential Carcinogen</u>	<u>NTP:</u>	<u>IARC:</u>	<u>OSHA:</u>
Health Hazard (Acute or Chronic)	N/A	N/A	N/A
Skin :	Not anticipated to be a primary skin irritant based upon available data.		
Eyes :	Not anticipated to be a primary eye irritant based upon available data.		
Ingestion :	Human ingestion Hazard not known.		
Inhalation :	Not hazardous under normal use conditions.		
Effect of Over Exposure :	Central nervous system depression; likely route - inhalation. Deliberately concentrating and inhaling content can lead to unconsciousness and/or death.		
Medical Conditions Generally Aggravated by Exposure :	Existing pulmonary or dermal condition.		

Emergency And First Aid Procedures

Skin : Wash with soap and water. Consult physician if irritation occurs and persists.
Eyes : Wash with water. Consult physician if irritation occurs.
Ingestion : Consult physician at once. Do not induce vomiting.
Inhalation : Removing victim from exposure. Alert emergency medical personnel. Administer artificial respiration if breathing is stopped.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE

Spill or Leak Procedures : Handle as flammable liquid and dispose of properly. Ventilate area.
Disposal Recommendations : Dispose in accordance with local, state, and federal