



Product Identification	White Ink Jet Printer Mailing Labels
Product SKU's	72782 08461
Product Specifications: Total Caliper Face Material and Adhesive Backing	0.00825 inches $\pm$ 10% 0.0050 inches $\pm$ 10% White Uncoated Paper 0.00345 inches $\pm$ 10% White Uncoated Kraft Paper
Adhesive Capabilities: Adhesive Type Adhesive Reference Minimum Application Temperature Service Application Temperature Sunlight (UV) Resistance Plasticizer Resistance Heat Resistance Shelf Life Surface Recommendations	Emulsion Acrylic Permanent +25°F - 65°F to +200°F *Good Good Fair 3 years under normal shelf conditions Mailing Substrates: papers, envelopes, cardboard, corrugated board; **Other substrates: metals, painted metals, glass, plastics
Compliance: FDA CONEG Proposition 65 RoHS	Title 21, Section 175.105 of the Code of Federal Regulations (21 CFR 175.105). Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label. Complies
Environmental: Acid Free Archival Repulpable Recycled Content Post Consumer Waste	Yes Meets PAT Requirement based on ISO 10214, ISO 14523 and 18902; Meets ANSI NAPM IT9.16-1993 Meets USPS-P-1238F-recyclable requirement for Environmentally Benign Adhesives (EBA) None None
Safety/Toxicity:	
Other:	* Resistance to sunlight will vary depending on the types of inks used for printing. Toner for laser printing has good sunlight resistance. Face stock alone has good sunlight resistance for the duration of shelf life. ** Surface properties can vary due to different surface treatments. For specific applications technical experts must be consulted.