

Material Safety Data Sheet

May be used to comply with

OSHA's Hazard Communication Standard,

29 CFR 1910.1200. Standard must be

consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

IDENTITY(As Used on Label and List)

Specification for inkfilm for Brother facsimile

Fax 1350series (Accessories PC101,PC102RF,PC104RF)

Fax 000series (Accessories PC01,PC02RF,PC04RF,PC06)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I**Manufacturer's Name**

DAI NIPPON PRINTING CO.,LTD.

Emergency Telephone Number

042-952-9666

Address:591-2, Kamihirose, Higashikubo, Sayama,
Saitama, 350-1321
JAPAN**Telephone Number for information**

042-952-9666

Date prepared March 3, 1999**Signature of Preparer (optional)**

Hideichiro Takeda / Mgr. of Technical Dept.

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	%(optional)
Polyethylene terephthalate film (CAS No. 25038-59-9)				(47 ~ 51%)
Coating layer substances				
Carbon Black (CAS No. 1333-86-4)	3.5mg/m3	3.5mg/m3	None	(7~ 11%)
Ester Wax (CAS No. 8015-86-9)	-	-	None	(4~ 8%)
Paraffin Wax (CAS No. 8002-74-2)	-	2.0mg/m3	None	(11~ 15%)
Microcrystalline Wax (CAS No. 63231-60-7)	-	-	None	(13~ 19%)
Ethylene Vinyl Acetate Copolymer(CAS No. 24937-78-8)	-	-	None	(1~ 5%)
Others	-	-	None	(3~ 7%)

Section III - Hazardous Ingredients/Identity Information

Boiling Point	Not applicable	Specific Gravity (H2O=1)	About 1.2
Vapor Pressure (mmHg)	Not applicable	Melting Point	71°C
Vapor Density (AIR = 1)	Not applicable	Evaporation Rate (Butyl Acetate=1)	Negligible

Solubility in water

Negligible

Appearance and Odor

Ink is black solid with slight acetic acid odor.

Section IV - Fire and Explosion Hazard Data

Flash point (Method Used)	Flammable Limits	LEL	UEL
About 250°C for ink	Not applicable	Not applicable	Not applicable

Extinguishing Media

CO2, Water, Dry Chemicals, Foam

Special Fire fighting Procedures

For large quantities (i.e. truckload or pallet) involved in a fire, firefighters should wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion Hazards

None

(Reproduce locally)

OSHA 174, Sept. 1985

March 2, 1999

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	☐	None

Incompatibility (Materials to Avoid)
None

Hazardous Decomposition or Byproducts
CO, CO2, NOX and H2O etc.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	☐	None

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	No	No	possible but very unusual.

Health Hazards (Acute and Chronic)

All the ingredients are negative mutagenic (Test species ;S. typhimurium)

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	Carbon Black : Group 2B	No

Signs and Symptoms of Exposure
None

Medical Conditions

Generally Aggravated by Exposure None

Emergency and First Aid Procedures
Not applicable

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Rumpling the product may cause the wax layer to peel off. Sweep up or vacuum. When sweeping , avoid raising film or dust. If a vacuum is used , motor should be rated as dust tight. Wash any residue off skin with soap and water. Garments may be wasted or dry cleaned after removal of loose film or dust.

Waste Disposal Method

Dispose by the same method of ordinary plastic products in accordance with all applicable regulations. Any disposal practice must be in compliance with local, state and federal laws and regulations. If necessary, contact government office and ensure conformity with disposal regulations.

Precautions to Be Taken in Handling and Storing.

No special precautions for safety reason.

Other Precautions

None

Section VIII - Control Measures

Respiratory Protection (Specify Type)
Not required

Ventilation	Local Exhaust No	Special No
	Mechanical (General) No	Other No

Protective Gloves
Not required

Eye Protection
Not required

Other Protective Clothing or Equipment
None

Work/Hygienic Practices
None

(Reproduce locally)

OSHA174, Sept. 1985
March 2, 1999