

MATERIAL SAFETY DATA SHEET

Manufacturer

Wite-Out Products, Inc.
145 Southchase Blvd.
Fountain Inn, SC 29644

MSDS Preparer:

SGS U.S. Testing Company, Inc.*
Fairfield, NJ 07004
Tel: (973) 575-5252

*Specific Technical information
provided by manufacturer

Date: June 4, 2001

Supersedes: October 8, 1997

Page 1 of 3

Emergency Telephone No.
(800) 424-9300

Information Telephone No.
(203) 783-2103

I. PRODUCT INFORMATION

Identity : Wite-Out® For Everything® Correction Fluids (Quick Dry, Extra Coverage, Super Smooth)& Commercial Pack
Chemical Name : Not Available (N/A)
Chemical Family : N/A
CAS Registry Number : N/A
DOT Shipping Name : Coating Solution
DOT Hazard Class : Flammable Liquid

II. HAZARDOUS INGREDIENTS

<u>Component(s)</u>	<u>%</u>	<u>OSHA PEL</u>	<u>Hazard Information</u>	
			<u>ACGIH TLV</u>	<u>OTHERS</u>
Petroleum Naphtha (CAS #64742-48-9)	40	400mg/m ³	400mg/m ³	Flammable

III. PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point, °F : 204-237
Vapor Pressure (mm Hg) : 26-49 at 68°F
Vapor Density (Air = 1) : volatile components, 3.4 - 4.0 (Estimated)
Solubility in Water : Practically Insoluble (0.1 g/L)
Appearance and Odor : Free flowing liquid with petroleum solvent odor
Specific Gravity, (H₂O = 1) : Correction fluid 1.25
Melting Point : -8°F to +8°F
Evaporation Rate (Butyl Acetate = 1) : 0.89 - 1.08

IV. FIRE AND EXPLOSION HAZARD DATA

Flammable Liquid : Can release vapors that form flammable mixture at or above flash point.
Flash Point (Method Used) : 17-37°F (ASTM D-3828-87)
Flammability Limits in Air, LEL : 1.7
UEL : 12.3
Extinguishing Media for Fires : CO₂, Foam, Dry Chemical
Special Fire Fighting Procedures : Flammable liquid. Wear self-contained breathing apparatus.
Unusual Fire and Explosion Hazards : Toxic combustion gas may be formed as decomposition products.

V. REACTIVITY DATA

Stability : ☐ Unstable ☒ Stable
Conditions to Avoid : Heat source, sparks or flame.
Materials to Avoid : Strong oxidizing or reducing agents.
Hazardous Decomposition Products : Toxic fumes or gases.
Hazardous Polymerization Products : ☐ May Occur ☒ May Not Occur

VI. HEALTH HAZARD DATA

Carcinogen or Potential Carcinogen

NTP:
N/A

IARC:
N/A

OSHA:
N/A

Health Hazard (Acute or Chronic)

Skin : Not a primary skin irritant per the FHSA.
Eyes : Not an eye irritant per the FHSA.
Ingestion : Human Ingestion Hazard Not known.
Inhalation : Not hazardous under normal use conditions.
Effect of Over Exposure : Central nervous system depression; Likely route-inhalation.
Deliberately concentrating and inhaling content can lead to unconsciousness and/or death.

Medical Conditions Generally

Aggravated by Exposure : Existing pulmonary or dermal condition.

Emergency And First Aid Procedures

Skin : Wash with soap and water. Consult physician if irritation occurs and persists.
Eyes : Wash with water for at least 15 minutes, holding eye lids open. Consult physician if irritation occurs.
Ingestion : Consult physician at once. Do not induce vomiting.
Inhalation : Remove victim from exposure. Alert emergency medical personnel.
Administer artificial respiration if breathing is stopped.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE

Spill or Leak Procedures : Handle as flammable liquid and dispose of properly. Ventilate area.
Disposal Recommendations : Dispose in accordance with local, state, and federal regulations.
Storage and Handling Recommendations : Store and transport in closed container. Store in ventilated area. Avoid heat, fire and fumes.
Other Precautions : Keep away from children.

VIII. CONTROL MEASURES

Respiratory Protection	:	NIOSH/MSHA approved respirator with organic vapor cartridge if exposure limits are exceeded when handling bulk. None necessary under normal use conditions.
Ventilation	:	[] Local [X] Mechanical [] Special [] Other
Protective Gloves	:	Chemical resistant gloves when handling bulk. None necessary under normal use conditions.
Eye Protection	:	Not required except when handling bulk.
Other Protection Equipment or Clothing	:	None required.
Work Hygiene Practice	:	Standard good industrial hygiene practice recommended.

IX. REGULATORY INFORMATION

California Proposition 65	:	This product complies with the labeling requirement of the California Safe Drinking Water and Toxic Enforcement Act of 1986.
TSCA	:	The components in this product are listed on the TSCA inventory.
Others	:	This product does not contain chemicals known to deplete the ozone layer.

Wite Out Products, Inc. and SGS U.S. Testing Company Inc., the preparer of this MSDS, believe that the information contained herein (including data and statements) is accurate as of the date hereof. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and the information referred to herein are beyond the control of Wite Out Products, Inc. and SGS U.S. Testing Company Inc., the preparer of this MSDS, (references to Wite Out Products, Inc. and SGS U.S. Testing Company Inc., the preparer of this MSDS, including its divisions, affiliates, and subsidiaries), Wite Out Products, Inc. and SGS U.S. Testing Company Inc., the preparer of this MSDS, expressly disclaim any and all liability as to any results obtained or arising from any use of the product or such information. No statement made herein shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents.