

Corporate Headquarters
3305 Kashiwa Street
Torrance, California 90505
310/530-4445

Artline
Xstamper

[MSDS NO. EX5003E-000]

DATE Feb.26,2001 p. 1/3

MATERIAL SAFETY DATA SHEET

1. PRODUCT & COMPANY IDENTIFICATION

• **PRODUCT NAME**

X stamper Ink X-200
(Black, Red, Green, Blue, Purple,)

• **NAME OF MANUFACTURER/SUPPLIER**

Shachihata Inc.

• **NAME OF SECTION**

Research and Development Dept.

• **ADDRESS**

4-69,Amatuka-chou,Nishi-ku,Nagoya-shi,Aichi-ken,Japan

• **TELEPHONE NUMBER**

052/521/1466

• **FAX NUMBER**

052/521/1468

2. COMPOSITION/INFORMATION ON INGREDIENTS

• **SUBSTANCE / MIXTURE**

Mixture

• **INGREDIENTS**

CHEMICAL OR COMMON NAME(S)	CAS NO.	INGREDIENTS(wt.%)
Castor Oil Derivative		40.80
Ethyl alcohol	64-17-5	5.15
Glycolol Ether Group		5.15
Alcohol Group		5.15
Synthetic Resin		5.15
Synthetic Dye		5.15
		100

3. HAZARDS IDENTIFICATION

• **CLASS NAME OF HAZARDS CHEMICALS FOR MSDS IN JAPAN**

Flammable liquids

• **PHYSICAL AND CHEMICAL HAZARDS**

Flammable liquids

• **ADVERSE HUMAN HEALTH HAZARDS**

Harmful in contact with eye or if swallowed.

4. FIRST-AID MEASURES

• **EYE CONTACT**

立即 Immediately flush with plenty of water.
See medical advice immediately.

• **SKIN CONTACT**

拭 Wipe off with dry cloth and wash with mild soap.

• **INHALATION**

移動 Move to well ventilated place.

• **INGESTION**

見 See medical advice immediately.

5. FIRE-FIGHTING MEASURES**• SPECIFIC HAZARDS WITH REGARD TO FIRE-FIGHTING MEASURES**

In case of fire, use foam dry chemicals.

• EXTINGUISHING MEDIA

Dry chemical powder, foam or carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Wipe off with dry cloth.

7. HANDLING AND STORAGE**• HANDLING**

- Use only in the well-ventilated areas.
- Avoid contact with skin or eyes.
- Avoid inhalation and ingestion.
- Avoid high temp. and fire.

• STORAGE

- Store in a cool and dry location.
- Keep bottle tightly closed.
- Keep away from heat or sunlight.

8. EXPOSURE CONTROL / PERSONAL PROTECTION**• CONTROL PARAMETERS**

[Ethyl alcohol]

ACGIH TLV (1990-91) TWA 1000ppm(1880mg/m³)

OSHA PEL(1993) 1000ppm(1900mg/m³)

• ENGINEERING MEASURES

Not required.

• PERSONAL PROTECTIVE EQUIPMENT

Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES**• APPEARANCE AND ODOR**

Liquid, minor solvent odor.

• DENSITY(g/cm³) 1.0

• BOILING POINT No data available

• VOLATILE(wt.%) 5~10

• SOLUBILITY IN WATER Insoluble

10. PHYSICAL HAZARD(STABILITY AND REACTIVITY)

- FLASH POINT 40 (closed cup)
- AUTOIGNITION TEMPERATURE 380
- EXPLOSION LIMIT No data available.

11. TOXICOLOGICAL INFORMATION

• ACUTE TOXICITY

[Ethyl alcohol]

Oral	LD50	(rat)	7,060 mg/Kg
Inhalation	LC50	(rat)	20,000 ppm/10H

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATION

Disposal as usual industrial waste goods, soak up with absorbent materials follow all regulations in your country.

14. TRANSPORT INFORMATION

Follow all regulations in your country

UN NUMBER 1210

UN CLASS 3.3(Flammable liquids)

15. REGULATORY INFORMATION

Follow all regulations in your country.

16. OTHER INFORMATION

The information herein is given in good faith, but no warranty, express or implied, is made.
